

# PG505

## UTILITY PAPER MASKING TAPE

### DESCRIPTION

A paint contractor industry staple. Crepe paper masking tape coated with a pressure-sensitive natural rubber adhesive. Offers an excellent balance of quick stick, panel adhesion and holding properties. Not recommended for outdoor exposure.

### PRODUCT APPLICATION

For general purpose masking.

### GOVERNMENT COMPLIANCE

ASTM D6123, Type I  
C.I.D. A-A-883B Type I

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Crepe Paper
<b>Adhesive</b>	Natural Rubber/Resin
<b>Adhesion to Steel</b> (oz/in of width) PSTC-101	33 (9.0 N/25mm)
<b>Tensile Strength</b> (lbs/in of width) PSTC-131	20 (87.5 N/25mm)
<b>Elongation</b> (% at break) PSTC-131	10
<b>Total Thickness</b> (mils) PSTC-133	5.8 (0.147mm)
<b>Quick Stick</b> (oz/in of width) PSTC-5	
To Kraft	5 (1.4 N/25mm)
To Steel	11 (2.7 N/25mm)
<b>Operating Temperature Range</b>	+50°F ~ +200°F (+10°C ~ +93°C)
<b>Color</b>	Beige, Orange



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 04/16

